




AGM JUMP STARTER

PBI 2400HD ⚡ 12/24 V ⚡ 2400/1200 CA



+++

Rotomolded and unbreakable housing

Retractable handle and puncture-proof wheels

12 V accessory outlet also used for memory saver mode

Anderson connectors for voltage selection (12/24 V)

Heavy-duty curved clamps and double-insulated, ultra-flexible 50 mm² cable

Reverse polarity buzzer

Optional: Auxiliary connector for auxiliary cables

500 A fuse for short-circuit protection and 1 spare fuse



THE PBI RANGE



PBI 1812

PBI 200

PBI 201

PBI 2400 HD

TECHNICAL INFORMATION

MODEL	PBI 1812	PBI 200	PBI 201	PBI 2400 HD
PART NUMBER	94065001C	94065200C	94065201C	232008
VOLTAGE (DC)	12 V	12 V	12/24 V	12/24 V
CRANKING AMPS (CA)	700	900	1800/900	2400/1200
CABLE LENGTH	0,71 m	1,59 m	1,70 m	1,52 m
CABLE CROSS SECTION	21 mm ²	21 mm ²	33 mm ²	50 mm ²
AUTOMATIC CHARGER	0,7 A	2 A	2 A	4 A



PACKAGING INFORMATION

MODEL	PBI 1812	PBI 200	PBI 201	PBI 2400 HD
NET WEIGHT	9,25 kg	11,75 kg	20,8 kg	30,5 kg
DIMENSIONS (L x W x h) mm	330 x 170 x 363	360 x 150 x 440	425 x 230 x 455	475 x 290 x 550

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12 V							24 V					
			<125*	150	175	250	300	350	500	100	250	500	1000	1500	2000
			HP* = CHECK YOUR ENGINE HP - LEGEND: ■ NORMAL ■■ INTENSIVE												
94065001C	PBI 1812	12 V	■■	■	■										
94065200C	PBI 200	12 V	■■	■■	■	■									
94065201C	PBI 201	12/24 V	■■	■■	■■	■	■	■		■■	■■	■			
232008	PBI 2400 HD	12/24 V	■■	■■	■■	■■	■■	■■	■	■■	■■	■■	■	■	

Related Battery charger Part number:

PBI 1812

PBI 200

PBI 201

PBI 2400 HD

EU: 94065021

EU: 2299003058CZ

EU: 2299003058CZ

EU: 865124-A

UK: 94065022

UK: 2299003058GZ

UK: 2299003058GZ

UK: 865124-A + 976158