



## AGM JUMP STARTER

# PROPULSTATION ⚡ 24 V ⚙️ 3200 CA



+++

For heavy-duty start-ups

Robust shell case design 5 mm shatterproof polyethylene

Long and flexible cables with a double insulation. Also equipped with fully insulated clamps

The battery has an exceptionally high capacity to accumulate and disperse high-ampere energy



Large wheels for off-road situation

Equipped with an auxiliary connector for optional cable connection

The connector ensures an optimal recharge of the booster (5 magnetic poles)

The two 500 A fuses are directly accessible from the outside of the booster

# THE PROPULSTATION RANGE



PPS 12V  
800 CA



PPS 12V  
1200 CA



PPS 12/24V  
2400/1200 CA



PPS 12V  
6400 CA



PPS 12/24V  
3200/1600 CA



PPS 24V  
3200 CA

## TECHNICAL INFORMATION

MODEL	PPS 12 V 800	PPS 12 V 1200	PPS 12/24 V 2400/1200	PPS 12 V 6400	PPS 12/24 V 3200/1600	PPS 24 V 3200
PART NUMBER	521002	520003	520008	560004	560000	560003
VOLTAGE (DC)	12 V	12 V	12/24 V	12 V	12/24 V	24 V
CRANKING AMPS (CA)	800 A	1200 A	2400/1200 A	6400 A	3200/1600 A	3200 A
CABLE LENGTH	1,55 m	1,55 m	1,35 m	2,10 m	2,10 m	2,10 m
CABLE CROSS SECTION	35 mm <sup>2</sup>	50 mm <sup>2</sup>	50 mm <sup>2</sup>	70 mm <sup>2</sup>	70 mm <sup>2</sup>	70 mm <sup>2</sup>



## PACKAGING INFORMATION

MODEL	PPS 12 V 800	PPS 12 V 1200	PPS 12/24 V 2400/1200	PPS 12 V 6400	PPS 12/24 V 3200/1600	PPS 24 V 3200
NET WEIGHT	13,55 kg	17,50 kg	27,90 kg	75 kg	70 kg	70 kg
DIMENSIONS [ L x W x h ] mm	450 x 170 x 510	450 x 170 x 510	560 x 190 x 610	580 x 510 x 1100	580 x 510 x 1100	580 x 510 x 1100

## HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12 V							24 V						
			<125*	150	175	250	300	350	500	1000+	100	250	500	1000	1500	2000
			HP* = CHECK YOUR ENGINE HP - LEGEND: <span style="background-color: #cccccc;">■</span> NORMAL <span style="background-color: #333333;">■</span> INTENSIVE													
521002	PPS 800	12 V	■	■	■	■										
520003	PPS 1200	12 V	■	■	■	■	■	■								
520008	PPS 2400/1200	12/24 V	■	■	■	■	■	■	■	■	■	■	■	■		
560004	PPS 6400	12 V	■	■	■	■	■	■	■	■	■					
560000	PPS 3200/1600	12/24 V	■	■	■	■	■	■	■	■	■	■	■	■	■	
560003	PPS 3200	24V										■	■	■	■	

### RELATED PART NUMBER:

#### DOCKING STATION

DC Vehicle station - with DC cable

AC Workshop station - with charger AC/DC-230/12V

#### BATTERY CHARGER FOR DOCKING STATION AC

PPS 12V	PPS 12/24 V	12V Mobile	12/24 V Mobile	24 V Mobile
DC12	DC1224	DCM		
AC12	AC1224	ACM	ACM	ACM
12V-2 A PN: 522502	12V-3 A PN: 522504	12V-10 A PN: 522510	12V-7 A PN: 522507	12V-10 A PN: 845120-A