

ELECTRONIC CHARGERS

FLASHMEM 60 ⚡ 12 V 🔌 60 A



+++

Microprocessor-controlled

Reprogramming, flashing and car diagnostics

Selectable output voltage up to 14.8V

Protection against reverse polarity and short circuit

Protection against voltage error and overload

Supply permanent, stabilized high Amp current

Heavy-duty clamps

WET, AGM, LITHIUM LiFePO₄



THE FLASHMEM RANGE



FLASHMEM 60



FLASHMEM 100



FLASHMEM 120

TECHNICAL INFORMATION

MODEL	FLASHMEM 60	FLASHMEM 100	FLASHMEM 120
PART NUMBER	805650300	805650400	805650500
INPUT VOLTAGE	110-240 V, 50-60 Hz		
INPUT POWER	1100 W	1700 W	2100 W
OUTPUT VOLTAGE	12 V - 14,8 V	12 V - 14,8 V	12 V - 14,8 V
CHARGE CURRENT	5-60 A	10-100 A	10-120 A
CHARGE CAPACITY	5-600 Ah	10-1000 Ah	10-1200 Ah
MAINTENANCE CAPACITY	5-1800 Ah	10-3000 Ah	10-3600 Ah
CABLE LENGTH	2,50 m	2,50 m	2,50 m
	6,00 m (805650301)	6,00 m (805650401)	6,00 m (805650501)



PACKAGING INFORMATION

MODEL	FLASHMEM 60	FLASHMEM 100	FLASHMEM 120
NET WEIGHT	6,40 kg	8,20 kg	11,80 kg
DIMENSIONS (L x W x h) mm	400 x 340 x 215	440 x 375 x 240	440 x 375 x 240



MODEL	TROLLEY BM 200
PART NUMBER	895900100
NET WEIGHT	25,50 kg
DIMENSIONS (L x W x h) mm	540 x 560 x 1120