



## ELECTROMECHANICAL CHARGERS

SCI90 ⚡ 6/12V 🔌 3 / 5 / 20 A



+++

Fully automatic microprocessor-controlled charger

Auto voltage detection (6/12 V)

150A boost mode to help start dead batteries

Deep desulfation mode

Built-in digital voltmeter/tester – shows battery voltage & charging percentage

Float mode monitoring maintains optimum battery charge

Patented thermal runaway protection, monitors charge process to prevent battery from over heating

Reverse hook-up protection  
Helps protect battery and charger from damage

Protection against reverse polarity



 TECHNICAL INFORMATION

MODEL	SCI90
PART NUMBER	94065007C
VOLTAGE (DC)	6/ 12 V
INPUT VOLTAGE	230 V AC, 50-60 Hz
INPUT POWER	1400 W
VARIABLE CHARGE RATES	3 A / 5 A / 20 A
MAX. OUTPUT CURRENT ( During 3 sec )	90 A - 150 A
ENGINE START MODE (EMERGENCY STARTING)	√
CABLE LENGTH	1,75 m
BATTERY TYPES	AGM, GEL , CALCIUM and sulfated batteries


 PACKAGING INFORMATION

MODEL	SCI90
NET WEIGHT	5,82 kg
DIMENSIONS ( L x W x h ) mm	232 x 258 x 171

RELATED PART NUMBER:

FOOT FOR RUBBER BASE

4999000171