



## BATTERY CHARGER & MAINTAINER

**SPX 458** ⚡ **12V** 🔌 **3A**



Worry-free charging.  
Maintain all season.

+++

Battery charger and maintainer

For 12V batteries up to 58 Ah

Microprocessor controlled

Protection against: Reverse polarity, spark proof and thermal runaway

AGM, Standard, gel, calcium, Start n' Stop, Lithium (LiFePo4)

**IP 54:** Limited protection against dust ingress. Protection against splashing water from any direction.

Protective bumpers and hook attachment

Fully automatic and safety shut-off



# THE SPX RANGE



SPX 457

SPX 458

SPX 459

SPX 460

## TECHNICAL INFORMATION

MODEL	SPX 457	SPX 458	SPX 459	SPX 460
PART NUMBER	94065457*	94065458*	94065459*	94065460*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I			
VOLTAGE (DC)	6/12V	12V	12V	12V
NOMINAL AC VOLTAGE	230V AC - 50 Hz			
MAX. CHARGING CURRENT	1A	3A	6A	10A
IP RATING	IP66	IP54	/	/
BATTERY TYPE	Lead-Acid & Lithium	Lead-Acid & Lithium	Lead-Acid & Lithium	Lead-Acid & Lithium
OUTPUT CABLE (cm) (From enclosure to clamp end)	191	191	195	195
WORKING TEMPERATURE	-20° to +50° C			



## PACKAGING INFORMATION


MODEL	SPX 457	SPX 458	SPX 459	SPX 460
NET WEIGHT (Kg)	0,78	0,86	1,37	1,37
DIMENSIONS (L x W x H / mm)	131 x 101 x 204	105 x 137 x 210	163 x 136 x 218	163 x 136 x 218

 Schumacher®

Rue de la Baronnerie, 3  
4920 Harzé - Belgium

+32 4 388 20 17

info@schumachereurope.com  
www.schumachereurope.com

 @schumacherboosters

Since  
1947